



Brings you the best in Retail Technology

E-Touch SlimPoS II

E-Touch SlimPoS II is a slim design with small footprint for hospitality and retail industries. The simple stylish design with different platforms offers the customer a variable selection from the best price performance model to a high speed fanless model. The true flat touch panel provides customer the best touch experience. A Variety peripherals enhance customer usability.



Features



10.4" & 15" display with True Flat touch technology



A pole type 2nd display design with wide angle tilt



Resistive and P-Cap touch panel supported



HDD easy to swap



A fanless design to reduce noise and prevent dust inside the unit



Slim type MSR and VFD design

SPECIFICATIONS

Model Name	E-Touch SlimPoS II	
Processor	Intel Cedarview D2550 Dual Core 1.86G , L2 1M, 10W	Intel Ivy Bridge Celeron 1007U Dual Core 1.5G , LLC 2M, 17W
Chipset	CPU integrated graphic + NM10, 2W	CPU integrated graphic + HM76, 4.1W
System Memory	1 x DDR3 SO-DIMM up to 4GB, 1066MHz - 2 GB	1 x DDR3 SO-DIMM up to 8GB, 1600MHz - 2 GB
Graphic Memory	Intel GMA 3650 (Gfx frequency up to 640MHz), DX9	Intel HD graphic DX 11 and OCL1.1
LCD Touch Panel		
LCD Size	15" LED LCD	
Brightness	250~300 cd/m2	
Resolution	1024x768	
Touch Screen	Resistive touch / True flat resistive touch / True flat projected capacitive touch	
Tilt Adjustment	0° ~ 77°	
Storage Device		
Hard Drive	one 2.5" slim SATA HDD bay - 320 GB HDD	
Flash Memory	SATA SSD flash card (same location as HDD, Option)	
Expansion		
miniPCI-E Socket	1	
External I/O Ports		
USB	4 x USB Type A (USB 2.0)	6 x USB Type A (USB 3.0 / 2.0 x 2, USB 2.0 x 4)
Serial Port	4 x RJ45 COM ports (COM1 standard RS232; COM2/3/4 powered RS232; COM2 default 0V; COM3 default 5V; COM4 default 12V by BIOS setting)	3 x RJ45 COM ports (COM1/2/3 powered RS232; COM1 default 5V; COM2 default 5V; COM3 default 12V by BIOS setting)
GigaLAN (10/100/1000)	1 (RJ45)	
Cash Drawer	1 (RJ11)	
2nd VGA	1 (DB15 Female)	
DC Jack	1	
Power Switch	1	
Control / Indicator		
Power Button	1	

Power		
Power Supply	65W/19V-4 pin with Lock	90W/19V-4 pin with Lock
Peripheral (option)		
MSR	3 Tracks (USB)	
iButton	iButton (USB)	
Finger Print Reader	Finger Print Reader (USB)	
Second Display	10.4" / 15" 2nd display without touch	
Customer Display	LCM display 2 x 20 characters (USB) / Tilt angle: 10° (Up), 24° (Down), 25° (Right), 25° (Left)	
Certificate		
EMC & Safety	FCC Class A / CE Mark / LVD	
Environment		
Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)	
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)	
Humidity	20% ~ 85% RH non-condensing	
Communication		
Wireless LAN	802.11 b/g/n WLAN card	
Dimension (WxDxH)	370 x 220 X 298 mm (14.6" x 8.7" x 11.3")	
Weight	7.5kg (16.5lbs)	
OS Supported	Windows Embedded POSReady 2009, Windows XP Professional for Embedded, Windows 7	

