



Brings you the best in Retail Technology

E-Touch Xtreme II

The Xtreme II of the Xtreme Series, is designed to either be a POS Terminal or a Panel PC Sporting a more modern feel, it also is equipped with a 15" True Flat Touch panel hence enhancing its streamline shape. No matter which role it plays, the Xtreme II was born with Perfection,

A perfect Candidate for a variety of Applications and Harsh Environments,

With its Die Cast Technology the Xtreme II becomes a good contender for harsh environments, the Xtreme II would applies die casting technology to its stand so as to give carefree utilization.



White or Black

- Borderless design with True Flat Touch Technology
- Rugged housing made by aluminum die-casting
- Fanless terminal and low power consumption

Features



P-Cap Multi-Touch



Magnetic Strip Card Reader



Variety of peripherals



Fingerprint & IButton selectable



Slide In/out HDD replacement



Stand with adapter housing and cable management

Specification		
Model Name	E-Touch Xtreme II	
Motherboard	D36	D66
Processor	Intel Bay Trail CPU Celeron J1900 2.0 GHz, L2 2MB, 10W (Default - Celeron J1900 2.0 GHz)	Intel Haswell CPU LGA-1150 22nm i5-4570S 2.9GHz, LLC 6MB, TDP 65W, AMT 9.0 i3-4330 3.5GHz, LLC 4MB, TDP, 54W Pentium G3420 3.2GHz, LLC 3M, TDP, 54W Celeron G1820 2.7G L3 2M, 53W (Default - Haswell i3-4330 3.5 GHz)
Chipset	N/A	
System Memory	1 x DDR3 1066 / 1333MHz SDRAM up to 8GB (Default – 2 GB RAM)	1 x DDR3 1333 / 1600MHz SDRAM up to 8GB (Default – 4 GB RAM)
Graphic Memory	Intel Gen7@>300MHz	Intel HD Graphic DX11.1
LCD Touch Panel		
LCD Size	15" TFT LCD	
Brightness	250 cd/m ²	
Resolution	1024x768	
Touch Screen	Resistive touch or True Flat resistive and P-CAP touch	True Flat resistive and P-CAP touch
Tilt Adjustment	0° ~ 90°	
Storage Device		
Hard Drive	1 x 2.5" SATA HDD (Default – 320 GB HDD)	
Flash Memory	1 x SATA SSD card (Option)	
Expansion		
miniPCI-E Socket	1	
External I/O Ports		
USB 2.0	4	
USB 2.0/3.0	1	2
Serial Port	3 x RJ45 COM ports (COM1 and COM2 +5V, COM3 +12V, power enabled by BIOS setting)	
Parallel Port	1 (Option)	
GigaLAN (10/100/1000)	1 (RJ45)	
VGA	1 (12V enabled by BIOS setting)	
Cash Drawer	1 (RJ11)	
Audio Line-out	1 (Option)	
DC Jack	1	
Audio		
Internal Speaker	2 x 2W speakers (Option)	
Power		
Power Supply	65W/19V	120W/19V

Control / Indicator		
Power Button		1
Indicator LED		1
Peripheral (option)		
MSR		3 Tracks MSR (USB)
Second Display		8.4" / 15" without touch
Customer Display		Flush mount VFD display 2 x 20 characters (COM)
iButton		Same location either iButton (USB) or Fingerprint option
Finger print		Digital Persona module (USB)
Certificate		
EMC & Safety		FCC Class A / CE Mark / LVD
Environment		
Operating Temperature		0 °C ~ 35 °C (32 °F ~ 95 °F)
Storage Temperature		-20 °C ~ 60 °C (-4 °F ~ 140 °F)
Humidity		20% ~ 85% RH non-condensing
Communication		
Wireless LAN		802.11 b/g/n wireless LAN card & antenna (Option)
Color		Black / Shiny white
Dimension (WxDxH)		LCD 90° tilt angle: 361 x 248 x 337 mm (14.2" x 9.8" x13.3")
Weight		8kg (17.6lbs)
Mounting		100 x 100 mm VESA mounting hole for panel PC type
OS Supported	Windows embedded 7 standard, Windows Embedded Compact 7, Windows 7, Windows embedded 8, Windows 8, Linux	POSReady 7, Windows® Embedded 8.1 Industrial Pro retail, Windows® Embedded 8.1 Industry Pro, Linux
Product specifications subject to change without prior notice.		

